

MATERIAL SAFETY DATA SHEET

Date of issue: Oct 10, 2011, Revision #3

MATERIAL SAFETY DATA SHEET

STACfill LT

HMIS & NFPA Hazard Ratings:

0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Extreme

Health=0	Flammability=1	Reactivity=0
----------	----------------	--------------

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: STACfill LT

Synonyms: Complex Mixture of paraffin waxes, polyisobutylene, calcium, silicate, Napthenic oils, closed cell cellular polymers, Petroleum derived hydrocarbon base.

General Use: For long-life corrosion protection, sealing and waterproofing of atmospheric buried and submerged metal surfaces. For application in cooler and/or cold atmospheric temperatures. A complementary component of the STACsystem, specially suitable for profiling irregular surfaces for gas utility, sewer, potable water, mining, and wastewater applications, and filling voids, before applying over wrapping of STACwrap and STACguard.

Company Identification:

Manufacturer:

Central Products (Tianjin) Co., Ltd.
B-H-E23 Houtai, Zhong Bei Industrial Park, Xiqing District
Tianjin 300384 P.R. China

Phone: +86-22-2379-3591

Importer:

PTY Enterprises
2201 Harbor St, Unit C
Pittsburg, CA 94565 USA

Phone: +1-510-414-9924

For emergencies in U.S.A., Call: +1-510-414-9924

MATERIAL SAFETY DATA SHEET

2. HAZARDS IDENTIFICATION

GHS Hazard Classification:

Hazard statements : Eyes: N/A
Ingestion: May cause irritation of digestive tract
Inhalation: N/A
Skin: May cause irritation on prolonged contact

Precautionary statements :

Respiratory: No special protection is needed working with solid material.
Protection from fumes or vapors from molten material may be necessary, using a suitable filter-type respirator.

Eyes: Chemical goggles

Ventilation: None required under normal use.

Protective Gloves: None required under normal use.

Other Protection: Wear Coveralls

Other hazards which do not result in classification: Do not store near flame, heat, or strong oxidizing agents. Avoid prolonged skin contact. Wash thoroughly after handling.

3. COMPOSITION / INFORMATION ON INGREDIENTS

APPEARANCE: Slight wax or paraffin odor, white speckled yellow pasty color, waxy feel, clumps easily formed and separated by hand at lower temperatures. Low density; appears to be heavier than actuality. Will float in water.

Chemical name	CAS#	Percent	EINECS/ELINCS
Paraffin Wax Fumes (if generated)	8002-74-2	N/A	N/A

4. FIRE FIGHTING MEASURES

Flash Point / Method: >232 deg C, 450 deg F (ASTM D-92)

Flammable: NA

Extinguished by: Foam, Water Fog, Water Spray, Dry Chemical, CO2

Special Fire Procedures: Cool exposed surfaces with water spray, while avoiding spreading any burning liquid. Remove any undamaged containers from fire area if you can do so without risk.

Unusual Fire/Explosion Hazard: None

5. ACCIDENTAL RELEASE MEASURES

Sweep up and package appropriately for disposal. In the case of a molten material spill, absorb with sand or other inert absorbent. Notify appropriate state/local agencies. Waste disposal should be in accordance with Federal, State, and local regulation.

MATERIAL SAFETY DATA SHEET

6. HANDLING AND STORAGE

Handling: Handle with care without damaging the products. Wash or wipe hands after handling. Avoid direct contact with eyes, skin, and clothing which may find difficult to remove the stains.

Storage:

Temperature : <30°C

General : Keep in a cool, dry, well ventilated place. Stable under normal conditions of handling and storage.

7. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory: No special protection is needed working with solid material.
Protection from fumes or vapors from molten material may be necessary, using a suitable filter-type respirator.

Eyes: Chemical goggles

Ventilation: None required under normal use.

Protective Gloves: None required under normal use.

Other Protection: Wear Coveralls

Exposure Limits:-

Ingredient	Weight %	Vapor Pressure mmHg 20F	OSHA PEL-TWA	ACGIH LV-TWA	313 Report Required
Paraffin Wax Fumes, Smoke (if Generated)	N/A	N/A	2.00 mg/m	2.00 mg/m	No

MATERIAL SAFETY DATA SHEET

8. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point Range:	N/A
Melting Point Range:	55-60 deg C, 130-140 deg F
Percent Volatile:	N/A
Vapor Pressure:	N/A
Evaporation Rate:	N/A
Vapor Density:	N/A
Appearance & Odor:	Slight waxy Odor, white speckled yellow color, waxy clumps
Solubility in Water:	Insoluble
Specific Gravity:	N/A

9. STABILITY AND REACTIVITY

Stability:	Stable
Conditions to Avoid:	Prolonged contact with strong oxidizing agents
Decomposition Hazard:	Thermal decomposition in air may yield carbon oxides, sulfur oxides, nitrogen
Polymerization Hazard:	None

10. DISPOSAL CONSIDERATIONS

Sweep up and package appropriately for disposal. In the case of a molten material spill, absorb with sand or other inert absorbent. Notify appropriate state/local agencies. Waste disposal should be in accordance with Federal, State, and local regulation.

MANUFACTURER DISCLAIMER:

Information herein is given in good faith and is, to the best of our knowledge and belief, accurate and reliable. However, since information herein was obtained in part from independent suppliers not under the direction and supervision of the manufacturer, the Company means no warranty or representations, express or implied, that the information is accurate, reliable, complete or representative. The Company warrants only that it has made no effort to censor (other than trade secrets) or conceal any deleterious aspects of its product. The data shown above in no way modifies, amends, or enlarges any specification or warranty.